SWAGING TOOL WITH RECHARGEABLE BATTERY TYPE C130-26 ELEC 14.4V



Die No.	Single Bite	Multi Bite	Part No.
1	•		D-C130-01
1.5			D-C130-015
2			D-C130-02
2.5	•		D-C130-025
3	•		D-C130-03
3.5	•		D-C130-035
4			D-C130-04
4.5			D-C130-045
5		•	D-C130-05

The new C130-26 ELEC Two Speed Hydraulic Swaging Tool with Rechargeable Battery

(Part No. D-C130 ELEC)

Compact, self contained and rapid two speed electro-hydraulic tool for swaging ferrules up to code 4 single bite and up to code 5 multibite.

Ergonomic design and light weight which enables swaging to be done one handed.

The head is rotatable between 180° and 360° and is of open throat design which makes swaging easy.

A electrical variator of speed is integrated in the trigger and the return of piston is operated by the release trigger. Automatic release with an audible 'click' when force of 130 kN is reached.

Unless otherwise requested the C130-26 ELEC comes complete with:-



Standard 1 Hour Charger. 12V and 14.4V. (220V*) Ni-MH & Ni-Cd. Dimensions: 190x90x80mm Weight: 0.54 Kg



The new technology of 14.4V-3.0 Ah Ni-MH batteries offers more power and efficiency. No memory effect and 100% recyclable.

Spare Battery Part No. D-D62E SB



Optional Extra's

Other Charger Options. 15 minute Fast Charger. Part No. D-D31 15FC

1 Hour Mobile Charger for cigar-lighter on Vehicle DC 12V or 24V. Part No. D-D31 MOBC

TECHNICAL DATA

HYDRAULIC TOOL	555 T # 15444 - Print (CONTO) (SEC.)
Art. No.:	D-C130 ELEC
Max. Swaging Pressure	130 kN
Swaging Capacity	Upto 4 S/Bite - 5 M/Bite
Stroke	26mm
Battery	14.4V 3.0 Ah
Weight	6.84 Kgs
Dimensions (mm)	385x305x95

These machines are for use with aluminium and copper ferrules. Only use in a low volume, non-production environment.